



Lite Line Interactive UPS

Single Phase Uninterruptible Power Supply

LITE series combine in a compact design all features to be the perfect line interactive for personal computer, printers, gaming and similar application use.



SECURITY
DEVICES



PC / GAMING
SYSTEMS



POS
SYSTEMS



TELEPHONE
SYSTEMS



AUDIO VIDEO
SYSTEMS



SHOPS /
RESTURANTS

ITAPOWER
Hottest Cutting Edge Solutions

www.itapower.it

LITE LINE INTERACTIVE UPS
600VA~3000VA



- **Compact size**
- **Excellent microprocessor control guarantees high reliability**
- **Boost and buck AVR for voltage stabilization**
- **Auto restart while AC is recovering**
- **Simulated sine wave output**
- **Off-mode charging**
- **Cold start function**
- **Generator compatible (option)**
- **Optional HID Power Device USB port**

Technical Specifications

MODEL	LITE 600	LITE 800	LITE 1000	LITE 1500	LITE 2000	LITE 3000
CAPACITY	600 VA / 360 W	800 VA / 480 W	1000 VA / 600 W	1500 VA / 900 W	2000 VA / 1200 W	3000 VA / 1800 W
INPUT						
Voltage	220/230/240 VAC					
Voltage Range	162-290 VAC					
Frequency Range	60/50 Hz (auto sensing)					
OUTPUT						
Voltage	220/230/240 VAC					
AC Voltage Regulation (Batt. Mode)	±10%					
Frequency Range (Batt. Mode)	60 Hz or 50 Hz ±1 Hz					
Transfer Time	Typical 2-6 ms					
Waveform (Batt. Mode)	Simulated Sinewave					
BATTERY						
Battery Type & Number	12 V/7 Ah x 1	12 V 9 Ah x 1	12 V/7 Ah x 2	12 V/9 Ah x 2	12 V/9 Ah x 2	12 V/10 Ah x 2
Typical Recharge Time	4-6 hours recover to 90% capacity					
INDICATORS						
AC Mode	Green lighting					
Battery Mode	Green flashing					
ALARM						
Battery Mode	Sounding every 10 seconds					
Low Battery	Sounding every second					
Overload	Sounding every 0.5 second					
Fault	Continuously sounding					
PROTECTION						
Full Protection	Overload, discharge, and overcharge protection					
PHYSICAL						
Dimension, D X W X H (mm)	320 x 130 x 182			397 x 146 x 205		
Net Weight (kgs)	4,2	4,9	8,2	10,4	11	14
ENVIRONMENT						
Humidity	0-90 % RH @ 0- 40°C (non-condensing)					
Noise Level	Less than 40dB					

Product specifications are subject to change without further notice

ITAPOWER s.r.l
 Viale Sondrio,7, 20124 Milan (Italy)
 + 39 02 954205361
 info@itapower.com
 www.itapower.com

